COLUMN DRILL
40mm
Type: Z5044

Features:

> Drilling Capacity - 45mm
> Gear driven
> Coolant
> Hand control feed
> Morse taper Nr4

		Model					
		Z5032	Z5032A	Z5040	Z5040A	Z5045	Z5045A
Max. drilling capacity		32mm		40mm		45mm	
Taper of spindle hole		M.T.3		M.T.4		M.T.4	
Max. travel of spindle		130mm					
Distance between the center of spindle And the surface of the vertical column		283mm		290mm			
Maximum distance between the spindle nose and the surface of working table		725mm					
Maximum distance between the Spindle nose and the base surface		1125mm					
Maximum travel of the supporting block of working table		600mm					
Maximum travel of spindle box		250 mm					
Dimensions of working table		380 mm×300mm					
Steps of spindle		6					
Speed of spindle (r/min)		50Hz:80;145;260;375;710;1250					
		60Hz:95;175;310;450;850;1500					
Feed steps of spindle			6		6		6
Feed speed of spindle (mm/r)			0.06;0.09 0.12;0.15 0.18;0.30		0.06;0.09 0.12;0.15 0.18;0.30		0.06;0.09; 0.12;0.15; 0.18;0.30
Dimensions of the base surface		417 mm×416mm					
Motor	Power (KW)	0.75		1.1		1.5	
	Voltage (V)	110/220/380					
	Speed(r/min)	1400					
Overall dimensions (L×W×H)		1850 mm×750 mm×1000mm					
Weight of machine (Kg)		430				450	